

## DS-D5022FC 22" LED Monitor

### Overview

DS-D5022FC is a reliable surveillance display with LED backlit technology, excellent color reduction and image processing, truly display the video details. Multiply interfaces are able to meet various surveillance environments, and build-in speaker is convenient to audio play. DS-D5022FC is an ideal choice for security and surveillance application.

### Key Features

- LED backlit technology with full HD 1920×1080
- Wide view angle: 170°(H)/160°(V)
- Image processing: 3D comb filter, 3D De-interlace, 3D noise reduction
- Multiply inputs: HDMI, VGA, BNC, audio in
- Multiply outputs: BNC, audio output
- Build-in speaker
- External video play via USB port
- High reliable components for 7×24 working
- VESA stand bracket

### Model:

DS-D5022FC



## DS-D5022FC 22" LED Monitor



### Specification

<b>Model</b>	DS-D5022FC
<b>Display</b>	
<b>Display Type</b>	LED-Backlit
<b>Screen Size</b>	22"
<b>Pixel Pitch(H×V)</b>	0.248mm × 0.248mm
<b>Max Resolution</b>	1920×1080
<b>Brightness</b>	250cd/m2 (Typical)
<b>Contrast</b>	1000:1
<b>Response Time</b>	5ms
<b>Color</b>	16.7M
<b>Viewing Angle</b>	Horizontal 170°, Vertical 160°
<b>Interface</b>	
<b>HDMI</b>	1
<b>VGA</b>	1
<b>BNC</b>	In × 1, Out × 1
<b>USB Port</b>	1
<b>Audio</b>	
<b>Audio Input</b>	1, 3.5 mm mini-jack
<b>Audio Output</b>	1, 3.5 mm mini-jack
<b>Speaker</b>	2W × 2
<b>Mounting</b>	
<b>VESA</b>	100mm × 100mm
<b>General</b>	
<b>Power Supply</b>	DC 12V/3.0A
<b>Consumption</b>	< 30W(on) < 0.5W(Standby)
<b>Operation Temperature</b>	0°C ~ 40 °C
<b>Operating Humidity</b>	10%~85% (No Condensation)
<b>Storage Temperature</b>	-20°C ~ 60°C
<b>Storage Humidity</b>	5%~95% (No Condensation)
<b>Dimension (W×H×D)</b>	511.4x313.0x45.4 (mm) 20.1x12.3x1.8(inch)
<b>Weight</b>	4.6Kg(Gross weight) , 3.2(Net weight)